

Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape



Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape




Features

- Dot-less lighting ensures smooth, uniform illumination for a premium look.
- 90+ CRI delivers vibrant, accurate color representation.
- Up to 753 lumens per foot for bright, efficient lighting.
- Ultra-flexible design with a slim profile for easy installation.
- Compatible with 0-10V, MLV, ELV, and smart wireless dimming options.
- Cuttable every 1.04 inches (26.5 mm) for precise customization.
- IP67 waterproof rating ensures durable performance indoors and outdoors.
- Backed by a 50,000-hour lifespan, a 6-year warranty, and UL/CE certification.

Specifications

Available Color Temperatures:




Input voltage:	24VDC
CRI:	90
Power:	5.8W/ft
Lumens:	753lm/ft
Cut Length:	1.04" (26.3mm)
Environment:	IP67
Dimensions (W x H):	0.47" x 0.18" (12 x 4.5mm)
Beam Angle:	150°
Maximum run:	25ft (145 Watts)
Lamp Life:	50,000 Hours
Operating Temp:	-4°F to 113°F (-20°C to 45°C)
Adhesive:	3M
Warranty:	5 years
Dimming Control:	• Incandescent • CFL/LED • MLV • ELV • 0-10V • Dimmer switch / wireless app & wall switch.



Connectors and Wire

Ordering Code	Description
1) Glow67-TT	0.47" (12mm) Tape to tape connector
2) Glow67-TW	0.47" (12mm) Tape to wire connector with a 11.8" lead wire
3) Glow67-EC	0.47" (12mm) End cap
4) Glow67-WC	0.47" (12mm) Wall Clip and Two Screws
5) Glow67-SS	Wet Location Silicone Sealant
6) WS-2P-15	15ft 2 Pin 15ft Wire Spool
7) WS-2P-250	250ft 2 Pin 250ft Wire Spool



150° Beam Angle



Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape





Performance Table

Ordering Code	Length	Voltage	CCT	CRI	Wattage	Lumens	Cuttable	IP Rating
Glow67								
Glow67-27-16	16.4ft	24VDC	2700K	90+	5.8W/ft	703lm/ft	1.04"	IP67
Glow67-30-16	16.4ft	24VDC	3000K	90+	5.8W/ft	723lm/ft	1.04"	IP67
Glow67-35-16	16.4ft	24VDC	3500K	90+	5.8W/ft	744lm/ft	1.04"	IP67
Glow67-40-16	16.4ft	24VDC	4000K	90+	5.8W/ft	753lm/ft	1.04"	IP67
Glow67-50-16	16.4ft	24VDC	5000K	90+	5.8W/ft	750m/ft	1.04"	IP67
Glow67-65-16	16.4ft	24VDC	6500K	90+	5.8W/ft	743lm/ft	1.04"	IP67
Glow67-27-164	164ft	24VDC	2700K	90+	5.8W/ft	703lm/ft	1.04"	IP67
Glow67-30-164	164ft	24VDC	3000K	90+	5.8W/ft	723lm/ft	1.04"	IP67
Glow67-35-164	164ft	24VDC	3500K	90+	5.8W/ft	744lm/ft	1.04"	IP67
Glow67-40-164	164ft	24VDC	4000K	90+	5.8W/ft	753lm/ft	1.04"	IP67
Glow67-50-164	164ft	24VDC	5000K	90+	5.8W/ft	750m/ft	1.04"	IP67
Glow67-65-164	164ft	24VDC	6500K	90+	5.8W/ft	743lm/ft	1.04"	IP67

Available with 30 days lead time

Mechanical Diagrams



150° Beam Angle



Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape



Channel Compatibility

Surface Mount



SL-103-S-94
Aluminum Finish
Width (outside): 0.59" (14.90mm)
Width (inside): 0.50" (12.70mm)
Height: 0.27" (6.86mm)
Length: 94" (2.38m)



SL-118-S-94
Aluminum Finish
Width (outside): 0.66" (16.70mm)
Width (inside): 0.48" (12.30mm)
Height: 0.31" (8.00mm)
Length: 94" (2.38m)



SL-118-B-94
Black Finish
Width (outside): 0.66" (16.70mm)
Width (inside): 0.48" (12.30mm)
Height: 0.31" (8.00mm)
Length: 94" (2.38m)



SL-118-BB-94
Black Finish
Width (outside): 0.66" (16.70mm)
Width (inside): 0.48" (12.30mm)
Height: 0.31" (8.00mm)
Length: 94" (2.38m)




SL-179-S-94
Aluminum Finish
Width (outside): 0.66" (16.70mm)
Width (inside): 0.48" (12.30mm)
Height: 0.60" (15.30mm)
Length: 94" (2.38m)



SL-179-B-94
Black Finish
Width (outside): 0.66" (16.70mm)
Width (inside): 0.48" (12.30mm)
Height: 0.60" (15.30mm)
Length: 94" (2.38m)



SL-430-S-94
Aluminum Finish
Width (outside): 0.93" (23.50mm)
Width (inside): 0.80" (20.30mm)
Height: 0.50" (12.80mm)
Length: 94" (2.38m)



SL-454-S-94
Aluminum Finish
Width (outside): 0.93" (23.50mm)
Width (inside): 0.80" (20.30mm)
Height: 0.39" (12.80mm)
Length: 94" (2.38m)




SL-314-S-94
Aluminum Finish
Width (outside): 0.80" (20.30mm)
Width (inside): 0.68" (17.50mm)
Height: 0.80" (20.30mm)
Length: 94" (2.38m)




SL-331-S-94
Aluminum Finish
Width (outside): 1.14" (29.00mm)
Width (inside): 0.68" (17.50mm)
Height: 0.88" (22.35mm)
Length: 0.94" (2.44mm)




SL-504-S-94
Aluminum Finish
Width (outside): 1.31" (33.20mm)
Width (inside): 1.18" (30.00mm)
Height: 0.57" (14.40mm)
Length: 94" (2.38m)




SL-910-S-94
Aluminum Finish
Width (outside): 1.44" (36.70mm)
Width (inside): 1.18" (30.00mm)
Height: 1.44" (36.70mm)
Length: 94" (2.38m)



SL-910-B-94
Black Finish
Width (outside): 1.44" (36.70mm)
Width (inside): 1.18" (30.00mm)
Height: 1.44" (36.70mm)
Length: 94" (2.38m)



SL-928-S-94
Aluminum Finish
Width (outside): 1.97" (50.00mm)
Width (inside): 1.80" (45.72mm)
Height: 1.16" (29.50mm)
Length: 94" (2.38m)



SL-928-B-94
Black Finish
Width (outside): 1.97" (50.00mm)
Width (inside): 1.80" (45.72mm)
Height: 1.16" (29.50mm)
Length: 94" (2.38m)

Corner LED Channel




SL-214-S-94
Aluminum Finish
Width (outside): 0.64" (16.30mm)
Width (inside): 0.44" (11.00mm)
Height: 0.64" (16.30mm)
Length: 94" (2.38m)



SL-267-S-94
Aluminum Finish
Width (outside): 0.69" (17.70mm)
Width (inside): 0.47" (12.10mm)
Height: 0.69" (17.70mm)
Length: 94" (2.38m)

Recessed Mount




RL-601-S-94
Aluminum Finish
Width (outside): 0.91" (23.00mm)
Width (inside): 0.48" (12.30mm)
Height: 0.31" (8.00mm)
Length: 94" (2.38m)




RL-615-S-94
Aluminum Finish
Width (outside): 0.91" (23.00mm)
Width (inside): 0.48" (12.30mm)
Height: 0.57" (14.50mm)
Length: 94" (2.38m)




RL-727-S-94
Aluminum Finish
Width (outside): 1.20" (30.60mm)
Width (inside): 0.80" (20.30mm)
Height: 0.50" (12.80mm)
Length: 94" (2.38m)



RL-778-S-94
Aluminum Finish
Width (outside): 1.31" (33.20mm)
Width (inside): 1.18" (30.00mm)
Height: 0.57" (14.40mm)
Length: 94" (2.38m)



RL-809-S-94
Aluminum Finish
Width (outside): 1.43" (36.30mm)
Width (inside): 1.30" (33.10mm)
Height: 1.38" (35.00mm)
Length: 94" (2.38m)



RL-851-S-94
Aluminum Finish
Width (outside): 2.52" (64.00mm)
Width (inside): 1.57" (40.00mm)
Height: 1.16" (29.50mm)
Length: 94" (2.38m)

Trimless Mud-In



TL-041-S-94
Aluminum Finish
Width (outside): 0.93" (23.50mm)
Width (inside): 0.80" (20.50mm)
Height: 0.61" (15.50mm)
Length: 94" (2.38m)



TL-066-S-94
Aluminum Finish
Width (outside): 1.44" (36.70mm)
Width (inside): 1.18" (30.00mm)
Height: 0.61" (15.50mm)
Length: 94" (2.38m)



TL-071-S-94
Aluminum Finish
Width (outside): 1.97" (50.00mm)
Width (inside): 1.77" (45.00mm)
Height: 0.61" (15.50mm)
Length: 94" (2.38m)

Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape



Recommended 24V LED Drivers

Phase Cut Dimmable (Incandescent / CLF / LED / MLV / ELV)

XRD Dimmable LED Driver Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
XRD-40W-24VDC	120VAC	24VDC	40W	Yes	IP21	6.20" x 1.85" x 1.35"
XRD-60W-24VDC	120VAC	24VDC	60W	Yes	IP21	6.20" x 1.85" x 1.35"
XRD-75W-24VDC	120VAC	24VDC	75W	Yes	IP21	6.20" x 1.85" x 1.35"
XRD-96W-24VDC	120VAC	24VDC	96W	Yes	IP21	6.20" x 1.85" x 1.35"

MX1 High Power Dimmable LED Driver Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
MX1-150W-24VDC	120VAC	24VDC	150W	Yes	IP65	6.57" x 3.85" x 1.64"
MX1-200W-24VDC	120VAC	24VDC	200W	Yes	IP65	6.57" x 3.85" x 1.64"

MX2 Multi-Output Dimmable LED Driver Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
MX2-192W-24VDC	120VAC	24VDC	96W x 2	Yes	IP65	3.96" x 1.61" x 7.67"
MX2-288W-24VDC	120VAC	24VDC	96W x 3	Yes	IP65	3.96" x 1.61" x 10.23"

MRD Dimmable LED Driver Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
MRD-40W-24VDC	120VAC	24VDC	40W	Yes	IP21	3.31" x 1.57" x 0.98"
MRD-60W-24VDC	120VAC	24VDC	60W	Yes	IP21	3.31" x 1.57" x 0.98"
MRD-75W-24VDC	120VAC	24VDC	75W	Yes	IP21	3.31" x 1.57" x 0.98"
MRD-96W-24VDC	120VAC	24VDC	96W	Yes	IP21	3.31" x 1.57" x 0.98"

0-10V Dimmable

NanoDrive 0-10V Dimmable LED Driver Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
NANO-40W-24VDC	120-277VAC	24VDC	40W	Yes	IP54	10.35" x 2.55" x 1.53"
NANO-60W-24VDC	120-277VAC	24VDC	60W	Yes	IP54	10.35" x 2.55" x 1.53"
NANO-96W-24VDC	120-277VAC	24VDC	96W	Yes	IP54	10.35" x 2.55" x 1.53"

Non-Dimmable

ELD Plug-in Series



Ordering Code	Input Voltage	Output Voltage	Max Load	Class	Environment	Dimensions
ELD-60W-24VDC-UL	120VAC	24VDC	60W	Yes	IP65	8" x 2.4" x 0.78"
ELD-100W-24VDC-UL	120VAC	24VDC	100W	Yes	IP65	8" x 2.4" x 0.78"
ELD-150W-24VDC-UL	120VAC	24VDC	150W	Yes	IP65	9.3" x 2.48" x 1.25"
ELD-200W-24VDC-UL	120VAC	24VDC	200W	Yes	IP65	9.3" x 2.48" x 1.25"