

MX2 Series

Multi-Output Class 2 Phase Cut Dimmable J-Box LED Driver



Features


- New Compact Design
- Multi-Channel UL listed Class 2
- Dimmable with any Incandescent/CLF/LED/MLV/ELV (leading or trailing edge) dimmer switch
- Dim down to 0.1%
- No minimum load required
- Can be fully loaded without derating
- IP65 rated for dry and wet locations
- Built-in junction box with multiple $\frac{7}{8}$ " knock-outs
- 6-year warranty

Dimming



Dimming Protocol:	Triac / ELV (Phase cut)
Min. Dimming Level:	0.1%
Dim to Off:	Yes
Dimming Curve:	Linear

Mechanical Overview

MX2-192W-24DC



MX2-288W-24DC



Applications

- LED strip
- LED tape
- Cove lights
- Linear lights
- Puck lights

MX2 Series

Multi-Output Class 2 Phase Cut Dimmable
J-Box LED Driver



Dimmable



IP65

24V
DC

Specifications

Input	Ordering Code:	MX2-192W-24DC	MX2-288W-24DC
Input Voltage Range:		120VAC +/- 5%	120VAC +/- 5%
Input Frequency:		50-60Hz	50-60Hz
Input Current:		1.86A max	2.79A max
Inrush Current:		11.8A	12.6A
Efficiency:		88%	88%
Power Factor:		0.94	0.94
THD:		< 20%(@100% load)	< 20%(@100% load)

Output

Output Voltage:	24VDC	24VDC
Max Load:	96W x 2 Channel	96W x 3 Channel
Output Current @ Max Load:	4A x 2 Channel	4A x 3 Channel
Turn on delay time:	35ms	35ms

Environmental

Operating Ambient Temp.:	40°F - 104°F (-40°C - 40°C)	40°F - 104°F (-40°C - 40°C)
Maximum Case Temp. (Tcase):	90°C	90°C
Ingress Protection (IP):	IP65	IP65
Cover type:	Screwless	Screwless
Expected Lifetime:	>50,000	>50,000

Protection

Over Temp Protection:	Yes / Hiccup Mode	Yes / Hiccup Mode
Over Load Protection:	Yes / Hiccup Mode	Yes / Hiccup Mode
Short Circuit Protection:	Yes / Hiccup Mode	Yes / Hiccup Mode

Enclosure

Dimensions:	7.79" x 3.22" x 1.64" (L*W*H)	10.98" x 3.22" x 1.64" (L*W*H)
Material:	Aluminum	Aluminum
Finish:	Black Powder Coat	Black Powder Coat
Connection type:	Lead Wire / J-box	Lead Wire / J-box
Weight:	1.76lbs	2.42lbs


MX2 Series

Multi-Output Class 2 Phase Cut Dimmable
J-Box LED Driver




Wiring Diagrams

ELV



TRIAC / MLV



MX2 Series

Multi-Output Class 2 Phase Cut Dimmable
J-Box LED Driver




Dimmable



Mechanical Diagrams

MX2-192W-24DC



MX2 Series

Multi-Output Class 2 Phase Cut Dimmable
J-Box LED Driver



Dimmable



Mechanical Diagrams

MX2-288W-24DC

